

What is claimed is:

1. A table comprising:
 - a support leg having an elongated channel extending longitudinally along at least a portion of said support leg and opening laterally outwardly from said support leg, said channel having an open end communicating with a top of said support leg;
 - a catch member extending across at least a portion of said channel; and
 - a worksurface supported by said top of said support leg.
2. The table of claim 1 wherein said worksurface further comprises a cutout, wherein said top of said support leg is connected to said worksurface at said cutout.
3. The table of claim 1 wherein said top of said support leg further comprises a socket, wherein a portion of said worksurface is received in said socket.
4. The table of claim 1 wherein said top of said support leg further comprises a support platform, wherein a bottom of said worksurface is supported on said support platform.
5. The table of claim 1 wherein said worksurface comprises a inwardly extending groove formed around at least a portion of the periphery thereof, and further comprising a bumper having an insert inserted into said groove.
6. The table of claim 1 wherein said channel has a first depth at a first location proximate said top of said support leg and wherein said channel has a second depth at a second location distal to said top of said support leg, wherein said first depth is greater than said second depth.

7. The table of claim 1 wherein said channel is defined by a depth, and wherein said depth of said channel is tapered along the length thereof.

8. The table of claim 1 wherein said support leg has an opening formed along one side of said channel, and wherein said catch member
5 comprises an insert portion inserted in said opening and a cross member extending from said insert portion across at least a portion of said channel.

9. The table of claim 8 wherein said opening in said support leg is a first opening, and wherein said support leg has a second opening formed along an opposite side of said channel opposite said first opening, and further
10 comprising a second catch member having an insert portion inserted in said second opening and a cross member extending from said insert portion across at least a portion of said channel, wherein said cross members of said first and second catch members extend across the entirety of the channel.

10. The table of claim 1 wherein said worksurface comprises a rear edge, wherein at least a portion of said rear edge has a concave contour.
15

11. The table of claim 1 wherein said support leg is made of glass filled polypropylene.

12. The table of claim 1 wherein said support leg further comprises a plurality of ribs formed in said channel.

13. A table comprising:
20 a support leg having an elongated channel extending longitudinally along at least a portion of said support leg and opening laterally outwardly from said support leg, said channel having an open end at a top of said support leg; and

25 a worksurface supported by said top of said support leg, wherein said worksurface has a cutout shaped to receive at least a portion of said top of said support leg with at least a portion of said channel nested in said cutout.

14. The table of claim 13 wherein cutout is located at a corner of said worksurface.

5 15. The table of claim 13 wherein said top of said support leg further comprises a socket, wherein a portion of said worksurface is received in said socket.

16. The table of claim 13 wherein said top of said support leg further comprises a support platform, wherein a bottom of said worksurface is supported on said support platform.

10 17. The table of claim 13 wherein said worksurface comprises a inwardly extending groove formed around at least a portion of the periphery thereof, and further comprising a bumper having an insert inserted into said groove.

15 18. The table of claim 13 wherein said channel is defined by a depth, and wherein said depth of said channel is tapered along the length thereof.

19. The table of claim 13 further comprising a catch member extending across at least a portion of said channel.

20 20. The table of claim 19 wherein said support leg has an opening formed along one side of said channel, and wherein said catch member comprises an insert portion inserted in said opening and a cross member extending from said insert portion across at least a portion of said channel.

21. The table of claim 13 wherein said worksurface comprises a rear edge, wherein at least a portion of said rear edge has a concave contour.

25 22. The table of claim 13 wherein said support leg comprises a plurality of ribs formed in said channel.

23. The table of claim 14 wherein said channel opens diagonally outwardly from said corner of said worksurface.

24. A table comprising:

at least four support legs, wherein at least two of said support legs terminate in casters and wherein at least two of said support legs terminate in glides;

a worksurface supported by said at least four support legs.

25. The table of claim 24 wherein said at least four support legs are made of glass filled polypropylene.

26. The table of claim 24 wherein each of said support legs has an elongated channel extending longitudinally along at least a portion of said support leg and opening laterally outwardly from said support leg, said channel having an open end communicating with a top of said support leg.

27. A method for routing a utility line on a table comprising:

providing said table comprising a support leg having an elongated channel extending longitudinally along at least a portion of said support leg and opening laterally outwardly from said support leg, said channel having an open end at a top of said support leg, and a worksurface supported by said top of said support leg, wherein said worksurface has a cutout shaped to receive at least a portion of said top of said support leg with at least a portion of said channel nested in said cutout;

providing a utility line having at least a portion disposed on a top of said worksurface; and

running said utility line from said top of said worksurface into said channel through said open end thereof.

28. The method of claim 27 wherein said support leg comprises a catch member extending across at least a portion of said channel, and wherein said running said utility line further comprises running said utility line in said

channel behind said catch member and thereby capturing said utility line in said channel.

29. The method of claim 27 wherein said worksurface comprises a rear edge at least a portion of which has a concave contour and wherein said utility line comprises a plurality of utility lines, and further comprising passing one of said plurality of utility lines from said top of said worksurface over said rear edge at said portion thereof having a concave contour.

30. The method of claim 29 further comprising providing a trough disposed along said rear edge, and disposing said utility line passing over said rear edge in said trough.

31. A table comprising:
a support leg;
a worksurface supported by said support leg, wherein said worksurface comprises an upper surface and a rear edge, wherein at least a portion of said rear edge has a concave contour; and
a trough disposed along said rear edge below said upper surface of said worksurface.

32. The table of claim 31 wherein said trough is attached to said worksurface.

33. A system of tables comprising:
a first table comprising a support leg and a worksurface supported by said support leg, wherein said worksurface comprises an upper surface and a rear edge, wherein at least a portion of said rear edge has a concave contour; and

a second table comprising a support leg and a worksurface supported by said support leg, wherein said worksurface comprises an upper surface and a rear edge, wherein at least a portion of said rear edge has a concave contour, wherein said second table is positioned adjacent said first

table with said rear edges thereof substantially abutting, wherein said portions of said rear edges having said concave contours form an opening between said first and second table.

- 5 34. The system of claim 33 wherein each of said first and second tables comprise a trough disposed along said rear edge of each of said tables below said upper surface of said worksurface of each of said tables.

1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100